

INDOOR UNITS

Wall



OPTIONAL



<RC INCLUDED>

SRK 71-80 ZR-W

Model			SRK 71 ZR-W	SRK 80 ZR-W
Type			Indoor wall unit	
Control (included)			Remote control	
Rated heating	Cooling	kW	7.10	8.00
	Heating	kW	8.00	9.00
Electrical data				
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz	
Connection wires between I.U. and O.U.		no.	4	4
Refrigerant circuit				
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø15.88(5/8")	ø6.35(1/4") - ø15.88(5/8")
Product specifications				
Dimensions	LxDxH	mm	1197x262x339	1197x262x339
Net weight		Kg	15.5	16.5
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	44/41/37/25	47/44/39/26
	Heating		46/39/35/28	47/41/36/29
Sound power level (Hi)	Cooling	dB(A)	57	60
	Heating		60	62
Handled air volume (Hi/Me/Lo/ULo)	Cooling	m³/h	1230 / 1116 / 972 / 624	1410 / 1212 / 1050 / 624
	Heating		1500 / 1188 / 1038 / 798	1590 / 1278 / 1104 / 798
Motor power	Output	W	56	56
Condensate drain pipe	ø internal	mm	16	16
Optional parts				
Wi-Fi module ¹			AM-MHI-01	AM-MHI-01
Interface for home automation connection and wired control ²			SC-BIKN2-E	SC-BIKN2-E

¹ Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.

² Home automation and optional protocols with dedicated interfaces: KNX, Modbus, BACnet.

Wall



OPTIONAL



<RC INCLUDED>

SKM 20-25-35 ZSP-W

Model			SKM 20 ZSP-W	SKM 25 ZSP-W	SKM 35 ZSP-W
Type			Indoor wall unit		
Control (included)			Remote control		
Rated heating	Cooling	kW	2.00	2.50	3.50
	Heating	kW	3.00	3.40	4.50
Electrical data					
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz		
Connection wires between I.U. and O.U.		no.	4	4	4
Refrigerant circuit					
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")
Product specifications					
Dimensions	LxDxH	mm	783x210x267	783x210x267	783x210x267
Net weight		Kg	7.5	7.5	7.5
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	42/35/22	43/36/23	44/37/25
	Heating		41/36/26	41/36/27	42/37/30
Sound power level (Hi)	Cooling	dB(A)	57	57	58
	Heating		56	56	58
Handled air volume (Hi/Me/Lo/ULo)	Cooling	m³/h	510 / 510 / 420	510 / 510 / 420	540 / 540 / 450
	Heating		480 / 480 / 420	480 / 480 / 420	510 / 510 / 420
Motor power	Output	W	30	30	30
Condensate drain pipe	ø internal	mm	16	16	16
Optional parts					
Wi-Fi module			INWFIUN001000		
Interface for home automation connection and wired control			Not available for this product		