

# PORTABLE DEHUMIDIFIER

## Maximum comfort in your everyday spaces

The TERMAL DTM-10 A dehumidifier has a compact geometry and essential design, creating the right degree of moisture in the room, depending on requirements, for small, medium and large spaces.

It is equipped with a condensate collection tank, with a see-through window to see the filling level and a connection for possible continuous condensate drainage.

Safety you control, thanks to the indicator light on the control panel that signals when the tank is full, with relative auto switch-off.



DTM-10 A

- Automatic defrost.
- Auto-restart: automatic re-start after a black-out.
- Air filter.
- Timer.
- Continuous dehumidifying.



Portable			DTM-10 A
Power		Ph/V/Hz	1/220~240/50
Rated dehumidifying capacity	30° C DB - RH 80%	L/d	10
Control			Electronic
Adjustment range (relative humidity)		%	40 ~ 60
Consumption		W	270
Rated current		A	1.6
Sound pressure level (Hi/Lo)		dB(A)	-/43
Treated air flow (Hi/Lo)		m³/h	-/100
Supplied tank capacity		L	2.0
Operating range		°C	5 ~ 35
Refrigerant	Type/qty.	Kg	R134A/0.07
Global warming potential	GWP	kg CO2 eq.	1430
Dimensions	LxDxH	mm	300x212x410
Net weight		Kg	10.7