


## INDOOR UNITS

### Low head ducted



SRR 25-35-50-60 ZS-W



<RC INCLUDED>

Model			SRR 25 ZS-W	SRR 35 ZS-W	SRR 50 ZS-W	SRR 60 ZS-W
<b>Type</b>			Indoor duct unit			
<b>Control</b>			Remote control			
Rated heating	Cooling	kW	2.50	3.50	5.00	6.00
	Heating	kW	3.40	4.50	5.80	6.80
<b>Electrical data</b>						
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Connection wires between I.U. and O.U.		no.	4	4	4	4
<b>Refrigerant circuit</b>						
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")	ø6.35(1/4") - ø12.74(1/2")
<b>Product specifications</b>						
Dimensions	LxDxH	mm	750x500x200	750x500x200	950x500x200	950x500x200
Net weight		Kg	20.5	20.5	24	24
Sound power level (Hi)	Cooling	dB(A)	56	57	59	60
	Heating		59	60	61	63
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	37/33/30/24	38/34/31/25	41/37/34/29	44/38/35/30
	Heating		40/37/34/28	42/38/35/29	43/39/37/32	45/41/38/33
Treated air volume (Hi/Me/Lo/ULo)	Cooling	m³/h	570/480/390/270	600/510/420/300	810/660/600/450	870/690/630/480
	Heating		600/540/480/360	630/570/510/390	840/750/660/510	900/780/690/540
Fan pressure head	Hi	Pa	35	35	50	50
<b>Optional parts</b>						
Wi-Fi module <sup>1</sup>			WF-RAC			
Interface for home automation connection and wired control <sup>2</sup>			SC-BIKN2-E			
Kit for recovery from bottom			UT-BAT1EF		UT-BAT2EF	

1 Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.

2 Home automation and optional protocols with dedicated interfaces: KNX, Modbus, BACnet.

## Console



SRF 25-35 ZS-W  
SRF 50 ZSX-W



<RC INCLUDED>

Model			SRF 25 ZS-W	SRF 35 ZS-W	SRF 50 ZSX-W
<b>Type</b>			Indoor console unit		
<b>Control</b>			Remote control		
Rated heating	Cooling	kW	2.50	3.50	5.00
	Heating	kW	3.40	4.50	5.80
<b>Electrical data</b>					
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz		
Connection wires between I.U. and O.U.		no.	4	4	4
<b>Refrigerant circuit</b>					
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")
<b>Product specifications</b>					
Dimensions	LxDxH	mm	860x238x600	860x238x600	860x238x600
Net weight		Kg	18	19	19
Sound power level (Hi)	Cooling	dB(A)	50	51	58
	Heating		51	52	58
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	38/32/29/25	40/35/33/29	46/38/33/28
	Heating		39/35/33/39	41/36/35/33	46/41/38/32
Treated air volume (Hi/Me/Lo/ULo)	Cooling	m³/h	540/456/402/348	552/468/438/384	690/576/444/396
	Heating		630/492/462/396	642/498/486/444	720/600/564/456
<b>Optional parts</b>					
Wi-Fi module <sup>1</sup>			WF-RAC		
Interface for home automation connection and wired control <sup>2</sup>			SC-BIKN2-E		

1 Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.

2 Home automation and optional protocols with dedicated interfaces: KNX, Modbus, BACnet.