

## INDOOR UNITS

### Medium head ducted



FDUM 50 VH



OPTIONAL

Compatible with **AIRZONE** systems

Model			FDUM 50 VH
<b>Type</b>			<b>Indoor duct unit</b>
Rated heating	Cooling	kW	5.00
	Heating	kW	5.80
<b>Electrical data</b>			
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz
Connection wires between I.U. and O.U.		no.	4
<b>Refrigerant circuit</b>			
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø12.74(1/2")
<b>Product specifications</b>			
Dimensions	LxDxH	mm	750x635x280
Net weight		Kg	29
Sound power level	Max	dB(A)	60
Sound pressure level	P-Hi/Hi/Me/Lo	dB(A)	37/32/29/26
Treated air volume	P-Hi/Hi/Me/Lo	m <sup>3</sup> /h	780/600/540/480
Fan pressure head	Std/Max	Pa	35/100
<b>Accessories</b>			
Wired remote control			RC-E5 / RC-EX3A / RC-EXZ3A / RCH-E3
IR remote control (KIT)			RCN-KIT4-E2
<b>Optional parts</b>			
Wi-Fi module			INWFIMHI001R000
Human sensor (KIT)			LB-KIT2
SUPERLINK II interface			SC-ADNA-E
Recovery filter (KIT)			UM-FL1EF

### Ceiling



FDE 50 VH



OPTIONAL

Model			FDE 50 VH
<b>Type</b>			<b>Indoor ceiling unit</b>
Rated heating	Cooling	kW	5.00
	Heating	kW	5.80
<b>Electrical data</b>			
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz
Connection wires between I.U. and O.U.		no.	4
<b>Refrigerant circuit</b>			
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø12.74(1/2")
<b>Product specifications</b>			
Dimensions	LxDxH	mm	1070x690x210
Net weight		Kg	28
Sound power level	Max	dB(A)	60
Sound pressure level	P-Hi/Hi/Me/Lo	dB(A)	46/38/36/31
Treated air volume	P-Hi/Hi/Me/Lo	m <sup>3</sup> /h	780/600/540/420
<b>Accessories</b>			
Wired remote control			RC-E5 / RC-EX3A / RCH-E3
IR remote control (KIT)			RCN-E-E3
<b>Optional parts</b>			
Wi-Fi module			INWFIMHI001R000
Human sensor (KIT)			LB-E
SUPERLINK II interface			SC-ADNA-E