

# INDOOR UNITS

## Wall



<RC INCLUDED>

SRK 71-80 ZR-WF

Model			SRK 71 ZR-WF	SRK 80 ZR-WF
<b>Type</b>			Indoor wall unit	
Control			Remote control	
Rated heating	Cooling	kW	7.10	8.00
	Heating	kW	8.00	9.00
<b>Electrical data</b>				
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz	
Connection wires between I.U. and O.U.		no.	4	4
<b>Refrigerant circuit</b>				
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø15.88(5/8")	ø6.35(1/4") - ø15.88(5/8")
<b>Product specifications</b>				
Dimensions	LxDxH	mm	1197x262x339	1197x262x339
Net weight		Kg	15.5	16.5
Sound power level (Hi)	Cooling	dB(A)	57	60
	Heating		60	62
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	44/41/37/25	47/44/39/26
	Heating		46/39/35/28	47/41/36/29
Treated air volume (Hi/Me/Lo/ULo)	Cooling	m³/h	1230/1116/972/624	1410/1212/1050/624
	Heating		1500/1188/1038/798	1590/1278/1104/810
<b>Optional parts</b>				
Wi-Fi module			Included	
Interface for home automation connection and wired control <sup>1</sup>			SC-BIKN2-E	

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

## Wall



<RC INCLUDED>

SKM 15-20-25-35 ZSP-W

Model			SKM 15 ZSP-W	SKM 20 ZSP-W	SKM 25 ZSP-W	SKM 35 ZSP-W
<b>Type</b>			Indoor wall unit			
Control			Remote control			
Rated heating	Cooling	kW	1.50	2.00	2.50	3.50
	Heating	kW	2.00	3.00	3.40	4.50
<b>Electrical data</b>						
Power	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Connection wires between I.U. and O.U.		no.	4	4	4	4
<b>Refrigerant circuit</b>						
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")
<b>Product specifications</b>						
Dimensions	LxDxH	mm	783x210x267	783x210x267	783x210x267	783x210x267
Net weight		Kg	7.5	7.5	7.5	7.5
Sound power level (Hi)	Cooling	dB(A)	57	57	57	58
	Heating		56	56	56	58
Sound pressure level (Hi/Me/Lo)	Cooling	dB(A)	42/35/22	42/35/22	43/36/23	44/37/25
	Heating		41/36/26	41/36/26	41/36/27	42/37/30
Treated air volume (Hi/Me/Lo)	Cooling	m³/h	510/420/300	510/420/300	510/420/300	540/450/300
	Heating		480/420/330	480/420/330	480/420/330	510/420/360
<b>Optional parts</b>						
Wi-Fi module			INWFIUNIO011000			
Interface for home automation connection and wired control			Not available for this product			