

REMOTE CONTROLS

Serial controls

SRK ZSX/ZS/ZR SRF ZS/ZSX SRR ZS



FUNCTIONS

- ON/OFF.
- Operating modes: auto, cooling, heating, dehumidifying and ventilation.
- Fan speed.
- HIGH POWER function.
- ECO function.
- SILENT function (not available for SRR models).
- Air distribution with vertical swing (not available for SRR models).
- Air distribution with horizontal swing (not available for SRR and SRF models).
- 3D AUTO function (not available for SRR and SRF models).
- NIGHT SETBACK function.
- Daily ON/OFF timer.
- Weekly timer.
- SLEEP.
- ALLERGEN CLEAR function (not available for SRR models).
- Key lock.
- Settings reset (ACL).
- Time setup.
- MENU button (only available for ZSX and ZS series models).

SRK ZTL



FUNCTIONS

- ON/OFF.
- Operating modes: auto, cooling, heating, dehumidifying and ventilation.
- Fan speed.
- Air distribution with vertical swing.
- Air distribution with horizontal swing.
- 3D AUTO function.
- HIGH POWER function.
- ECO function.
- SILENT function.
- FUZZY AUTO function.
- ALLERGEN CLEAR function.
- Self Clean operation.
- NIGHT SETBACK function.
- Daily ON/OFF timer.
- Child Lock.
- Brightness adjustment.

DETAIL OF THE CONTROL FUNCTIONS

- **HIGH POWER:** the unit runs at very high speed to quickly reach the temperature in the set cooling or heating mode.
- **ECO:** the set temperature will be automatically adjusted to avoid excessive cooling or heating.
- **SILENT:** reduction in the speed of the external fan and compressor.
- **3D AUTO:** automatic swing of the louvres (vertical and/or horizontal) according to the room temperature and the set temperature.
- **NIGHT SETBACK:** prevents the room temperature from falling below 10° C.
- **SLEEP:** night-time dampening function.
- **ALLERGEN CLEAR:** activation of anti-allergenic filter.
- **MENU:** button to adjust the brightness of the indicators on the indoor unit, to select the AUTO OFF function, CLEAN function and PRESET function.
- **AUTO OFF:** if there are still no people in the room after 1 hour (can be set from 1 to 2 hours via remote control), the air conditioner stops operation and goes into "stand-by" mode.
- **CLEAN:** this function identifies the automatic mould sanitisation program that can be carried out at the end of the machine's operating cycle.
- **PRESET:** activation of the operating mode in pre-set heating or cooling mode.

REMOTE CONTROLS

Serial controls

SKM ZSP



FUNCTIONS

- ON/OFF.
- Operating modes: auto, cooling, heating, dehumidifying and ventilation.
- Fan speed.
- HIGH POWER function.
- ECO function.
- Air distribution with vertical swing.
- Daily ON/OFF timer.
- SLEEP.
- CLEAN function.
- Settings reset (ACL).
- Clock setting.

INDIVIDUAL CONTROLS

Optional controls

WIRED REMOTE CONTROL WITH LCD DISPLAY RC-E5

Wired remote control with LCD display: this display is large and high-contrast for excellent display of information. The wired remote control is capable of controlling up to 16 indoor units.

Main functions:

- Weekly timer as standard.
- Built-in temperature sensor.
- Settable temperature fields.
- Data saving function.
- 4 fan speeds.
- Control for adjusting the static pressure. (for FDU and FDUM models).



SIMPLIFIED WIRED REMOTE CONTROL RCH-E3

Particularly suitable for use in hotels and small offices, it enables the selection of 3 different ventilation modes.

The simplified wired remote control is capable of controlling up to 16 indoor units.

Simple to use, it has the following essential buttons:

- On/Off.
- Mode.
- Temp. setting.
- Fan speed.
- Built-in temperature sensor.

