

# INDOOR UNITS

## DUCTED LOW STATIC PRESSURE



SRR 25-35-50-60 ZS-W



OPTIONAL




< REMOTE CONTROL >  
INCLUDED

Model			SRR 25 ZS-W	SRR 35 ZS-W	SRR 50 ZS-W	SRR 60 ZS-W
<b>Type</b>			Ducted type indoor unit			
<b>Control</b>			Remote control			
Rated capacity	Cooling	kW	2.50	3.50	5.00	6.00
	Heating	kW	3.40	4.50	5.80	6.80
<b>Electrical data</b>						
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Wiring cables I.U./O.U.		nb.	4	4	4	4
<b>Refrigerant circuit data</b>						
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 12.74(1/2")	6.35(1/4") - 12.74(1/2")
<b>Product specifications</b>						
Dimensions	LxDxH	mm	750x500x200	750x500x200	950x500x200	950x500x200
Net weight		Kg	20.5	20.5	24	24
Sound power level (Hi)	Cooling	dB(A)	56	57	59	60
	Heating		59	60	61	63
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	37/33/30/24	38/34/31/25	41/37/34/29	44/38/35/30
	Heating		40/37/34/28	42/38/35/29	43/39/37/32	45/41/38/33
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m <sup>3</sup> /h	570/480/390/270	600/510/420/300	810/660/600/450	870/690/630/480
	Heating		600/540/480/360	630/570/510/390	840/750/660/510	900/780/690/540
Fan static pressure	Std/Max	Pa	5/35	5/35	5/50	5/50
<b>Optional parts</b>						
Wi-Fi module <sup>1</sup>			WF-RAC			
Interface for home automation connection and wired control <sup>2</sup>			SC-BIKN2-E			
Kit for recovery from bottom			UT-BAT1EF		UT-BAT2EF	

1. Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.  
2. Home automation protocols available: KNX, Modbus, BACnet.

## CONSOLE



SRF 25-35 ZS-W  
SRF 50 ZSX-W



OPTIONAL



< REMOTE CONTROL >  
INCLUDED

Model			SRF 25 ZS-W	SRF 35 ZS-W	SRF 50 ZSX-W
<b>Type</b>			Floor type indoor unit		
<b>Control</b>			Remote control		
Rated capacity	Cooling	kW	2.50	3.50	5.00
	Heating	kW	3.40	4.50	5.80
<b>Electrical data</b>					
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz		
Wiring cables I.U./O.U.		nb.	4	4	4
<b>Refrigerant circuit data</b>					
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 12.74(1/2")
<b>Product specifications</b>					
Dimensions	LxDxH	mm	860x238x600	860x238x600	860x238x600
Net weight		Kg	18	19	19
Sound power level (Hi)	Cooling	dB(A)	50	51	58
	Heating		51	52	58
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	38/32/29/25	40/35/33/29	46/38/33/28
	Heating		39/35/33/39	41/36/35/33	46/41/38/32
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m <sup>3</sup> /h	540/456/402/348	552/468/438/384	690/576/444/396
	Heating		630/492/462/396	642/498/486/444	720/600/564/456
<b>Optional parts</b>					
Wi-Fi module <sup>1</sup>			WF-RAC		
Interface for home automation connection and wired control <sup>2</sup>			SC-BIKN2-E		

1. Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.  
2. Home automation protocols available: KNX, Modbus, BACnet.