

INDOOR UNITS

KIREIA Plus WALL



<INCLUDED>



<REMOTE CONTROL INCLUDED>

SRK 20-25-35-50-60 ZSX-WF(T)

Model			SRK 20 ZSX-WF(T)	SRK 25 ZSX-WF(T)	SRK 35 ZSX-WF(T)	SRK 50 ZSX-WF(T)	SRK 60 ZSX-WF(T)
Type			Wall type indoor unit				
Control			Remote control				
Rated capacity	Cooling	kW	2.00	2.50	3.50	5.00	6.00
	Heating	kW	3.00	3.40	4.50	5.80	6.80
Electrical data							
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz				
Wiring cables I.U./O.U.		nb.	4	4	4	4	4
Refrigerant circuit data							
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 12.74(1/2")	6.35(1/4") - 12.74(1/2")
Product specifications							
Dimensions	LxDxH	mm	920x220x305	920x220x305	920x220x305	920x220x305	920x220x305
Net weight		Kg	13	13	13	13	13
Sound power level (Hi)	Cooling	dB(A)	53	55	58	59	62
	Heating		55	56	58	62	63
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	38/31/24/19	39/33/25/19	43/35/26/19	44/39/31/22	48/41/33/22
	Heating		38/33/25/19	40/34/27/19	42/35/28/19	47/41/33/23	47/42/34/23
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m³/h	678/546/360/300	732/600/402/300	786/648/438/300	858/744/468/324	978/804/534/324
	Heating		732/618/432/324	768/660/468/324	834/708/516/324	1038/858/588/372	1068/822/654/372
Optional parts							
Wi-Fi module			Included				
Interface for home automation connection and wired control ¹			SC-BIKN2-E				

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

KIREIA WALL



<INCLUDED>



<REMOTE CONTROL INCLUDED>

SRK 15-20-25-35-50 ZS-WF(T)

Model			SRK 15 ZS-WF(T)	SRK 20 ZS-WF(T)	SRK 25 ZS-WF(T)	SRK 35 ZS-WF(T)	SRK 50 ZS-WF(T)
Type			Wall type indoor unit				
Control			Remote control				
Rated capacity	Cooling	kW	1.50	2.00	2.50	3.50	5.00
	Heating	kW	2.00	3.00	3.40	4.50	5.80
Electrical data							
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz				
Wiring cables I.U./O.U.		nb.	4	4	4	4	4
Refrigerant circuit data							
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 12.74(1/2")
Product specifications							
Dimensions	LxDxH	mm	870x230x290	870x230x290	870x230x290	870x230x290	870x230x290
Net weight		Kg	9.5	9.5	9.5	9.5	10
Sound power level (Hi)	Cooling	dB(A)	48	48	50	54	59
	Heating		50	50	53	56	60
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	34/25/22/19	34/25/22/19	36/28/23/19	40/30/26/19	46/36/29/22
	Heating		36/29/23/19	36/29/23/19	39/30/24/19	41/36/25/19	46/37/31/24
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m³/h	558/420/354/300	558/420/354/300	594/480/354/300	678/522/420/300	726/594/444/354
	Heating		600/510/390/354	600/510/390/354	678/522/402/354	738/660/420/336	834/672/546/444
Optional parts							
Wi-Fi module			Included				
Interface for home automation connection and wired control ¹			SC-BIKN2-E				

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.