

INDOOR UNITS

KIREIA Plus WALL



<INCLUDED>



<REMOTE CONTROL INCLUDED>

SRK 20-25-35-50-60 ZSX-WF(T)

| Model | | | SRK 20 ZSX-WF(T) | SRK 25 ZSX-WF(T) | SRK 35 ZSX-WF(T) | SRK 50 ZSX-WF(T) | SRK 60 ZSX-WF(T) |
|---|--------------|------------|-------------------------|-------------------------|-------------------------|--------------------------|--------------------------|
| Type | | | Wall type indoor unit | | | | |
| Control | | | Remote control | | | | |
| Rated capacity | Cooling | kW | 2.00 | 2.50 | 3.50 | 5.00 | 6.00 |
| | Heating | kW | 3.00 | 3.40 | 4.50 | 5.80 | 6.80 |
| Electrical data | | | | | | | |
| Power supply | Outdoor unit | Ph-V-Hz | 1-220~240V-50Hz | | | | |
| Wiring cables I.U./O.U. | | nb. | 4 | 4 | 4 | 4 | 4 |
| Refrigerant circuit data | | | | | | | |
| Diameter of refrigerant pipings liquid/gas | | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") | 6.35(1/4") - 12.74(1/2") |
| Product specifications | | | | | | | |
| Dimensions | LxDxH | mm | 920x220x305 | 920x220x305 | 920x220x305 | 920x220x305 | 920x220x305 |
| Net weight | | Kg | 13 | 13 | 13 | 13 | 13 |
| Sound power level (Hi) | Cooling | dB(A) | 53 | 55 | 58 | 59 | 62 |
| | Heating | | 55 | 56 | 58 | 62 | 63 |
| Sound pressure level (Hi/Me/Lo/ULo) | Cooling | dB(A) | 38/31/24/19 | 39/33/25/19 | 43/35/26/19 | 44/39/31/22 | 48/41/33/22 |
| | Heating | | 38/33/25/19 | 40/34/27/19 | 42/35/28/19 | 47/41/33/23 | 47/42/34/23 |
| Air flow volume (Hi/Me/Lo/ULo) | Cooling | m³/h | 678/546/360/300 | 732/600/402/300 | 786/648/438/300 | 858/744/468/324 | 978/804/534/324 |
| | Heating | | 732/618/432/324 | 768/660/468/324 | 834/708/516/324 | 1038/858/588/372 | 1068/822/654/372 |
| Optional parts | | | | | | | |
| Wi-Fi module | | | Included | | | | |
| Interface for home automation connection and wired control ¹ | | | SC-BIKN2-E | | | | |

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

KIREIA WALL



<INCLUDED>



<REMOTE CONTROL INCLUDED>

SRK 15-20-25-35-50 ZS-WF(T)

| Model | | | SRK 15 ZS-WF(T) | SRK 20 ZS-WF(T) | SRK 25 ZS-WF(T) | SRK 35 ZS-WF(T) | SRK 50 ZS-WF(T) |
|---|--------------|------------|-------------------------|-------------------------|-------------------------|-------------------------|--------------------------|
| Type | | | Wall type indoor unit | | | | |
| Control | | | Remote control | | | | |
| Rated capacity | Cooling | kW | 1.50 | 2.00 | 2.50 | 3.50 | 5.00 |
| | Heating | kW | 2.00 | 3.00 | 3.40 | 4.50 | 5.80 |
| Electrical data | | | | | | | |
| Power supply | Outdoor unit | Ph-V-Hz | 1-220~240V-50Hz | | | | |
| Wiring cables I.U./O.U. | | nb. | 4 | 4 | 4 | 4 | 4 |
| Refrigerant circuit data | | | | | | | |
| Diameter of refrigerant pipings liquid/gas | | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") |
| Product specifications | | | | | | | |
| Dimensions | LxDxH | mm | 870x230x290 | 870x230x290 | 870x230x290 | 870x230x290 | 870x230x290 |
| Net weight | | Kg | 9.5 | 9.5 | 9.5 | 9.5 | 10 |
| Sound power level (Hi) | Cooling | dB(A) | 48 | 48 | 50 | 54 | 59 |
| | Heating | | 50 | 50 | 53 | 56 | 60 |
| Sound pressure level (Hi/Me/Lo/ULo) | Cooling | dB(A) | 34/25/22/19 | 34/25/22/19 | 36/28/23/19 | 40/30/26/19 | 46/36/29/22 |
| | Heating | | 36/29/23/19 | 36/29/23/19 | 39/30/24/19 | 41/36/25/19 | 46/37/31/24 |
| Air flow volume (Hi/Me/Lo/ULo) | Cooling | m³/h | 558/420/354/300 | 558/420/354/300 | 594/480/354/300 | 678/522/420/300 | 726/594/444/354 |
| | Heating | | 600/510/390/354 | 600/510/390/354 | 678/522/402/354 | 738/660/420/336 | 834/672/546/444 |
| Optional parts | | | | | | | |
| Wi-Fi module | | | Included | | | | |
| Interface for home automation connection and wired control ¹ | | | SC-BIKN2-E | | | | |

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.