

INDOOR UNITS

ULTRACOMPACT CASSETTE 60X60

R32



FDTC 25-35 VH1/FDTC 50-60 VH
Standard honeycomb panel
TC-PSA-5AW-E

FDTC 25-35 VH1/FDTC 50-60 VH
Anti-draft honeycomb panel
TC-PSAE-5AW-E

FDTC 25-35 VH1/FDTC 50-60 VH
Standard linear panel
TC-PSAG-5AW-E

FDTC 25-35 VH1/FDTC 50-60 VH
Anti-draft linear panel
TC-PSAGE-5AW-E

Model			FDTC 25 VH1	FDTC 35 VH1	FDTC 50 VH	FDTC 60 VH
Type			Cassette type indoor unit			
Rated capacity	Cooling	kW	2.50	3.50	5.00	6.00
	Heating	kW	3.40	4.50	5.80	6.80
Electrical data						
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Wiring cables I.U./O.U.		nb.	4	4	4	4
Refrigerant circuit data						
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 12.74(1/2")	6.35(1/4") - 12.74(1/2")
Product specifications						
Dimensions	LxDxH	mm	570x570x248	570x570x248	570x570x248	570x570x248
Net weight		Kg	13.5	13.5	14	14
Sound power level (Hi)	Cooling	dB(A)	51	52	59	60
	Heating		52	53	59	60
Sound pressure level (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	38/34/30/27	39/36/32/29	44/40/35/27	46/42/38/31
	Heating		39/36/32/28	41/38/34/30	44/40/35/27	46/42/38/31
Air flow volume (P-Hi/Hi/Me/Lo)	Cooling	m³/h	510/450/420/360	540/480/450/390	780/660/540/420	840/720/600/480
	Heating		570/510/450/390	600/540/480/420		
Accessories						
Decorative panel			TC-PSA-5AW-E (honeycomb) / TC-PSAG-5AW-E (linear)			
Panel size	LxDxH	mm	620x620x10	620x620x10	620x620x10	620x620x10
Net weight		Kg	2.5	2.5	2.5	2.5
Wired control			RC-E5 (LCD) / RC-EX3A (touch) / RCH-E3 (simplified)			
IR remote control (corner KIT)			RCN-TC-5AW-E3			
Optional parts						
Wi-Fi module			INWFIMH1001R100			
Human sensor (corner KIT)			LB-TC-5W-E			
SUPERLINK interface II			SC-ADNA-E			
Anti-draft panel			TC-PSAE-5AW-E (honeycomb) / TC-PSAGE-5AW-E (linear)			