

# INDOOR UNITS

## WALL



SRK 71-80 ZR-WF



<REMOTE CONTROL>  
INCLUDED

Model			SRK 71 ZR-WF		SRK 80 ZR-WF	
<b>Type</b>			Wall type indoor unit			
Control			Remote control			
Rated capacity	Cooling	kW	7.10		8.00	
	Heating	kW	8.00		9.00	
<b>Electrical data</b>						
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Wiring cables I.U./O.U.		nb.	4		4	
<b>Refrigerant circuit data</b>						
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 15.88(5/8")		6.35(1/4") - 15.88(5/8")	
<b>Product specifications</b>						
Dimensions	LxDxH	mm	1197x262x339		1197x262x339	
Net weight		Kg	15.5		16.5	
Sound power level (Hi)	Cooling	dB(A)	57		60	
	Heating		60		62	
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	44/41/37/25		47/44/39/26	
	Heating		46/39/35/28		47/41/36/29	
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m³/h	1230/1116/972/624		1410/1212/1050/624	
	Heating		1500/1188/1038/798		1590/1278/1104/810	
<b>Optional parts</b>						
Wi-Fi module			Included			
Interface for home automation connection and wired control¹			SC-BIKN2-E			

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

## WALL



SKM 15-20-25-35 ZSP-W



<REMOTE CONTROL>  
INCLUDED

Model			SKM 15 ZSP-W	SKM 20 ZSP-W	SKM 25 ZSP-W	SKM 35 ZSP-W
<b>Type</b>			Wall type indoor unit			
Control			Remote control			
Rated capacity	Cooling	kW	1.50	2.00	2.50	3.50
	Heating	kW	2.00	3.00	3.40	4.50
<b>Electrical data</b>						
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Wiring cables I.U./O.U.		nb.	4	4	4	4
<b>Refrigerant circuit data</b>						
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")
<b>Product specifications</b>						
Dimensions	LxDxH	mm	783x210x267	783x210x267	783x210x267	783x210x267
Net weight		Kg	7.5	7.5	7.5	7.5
Sound power level (Hi)	Cooling	dB(A)	57	57	57	58
	Heating		56	56	56	58
Sound pressure level (Hi/Me/Lo)	Cooling	dB(A)	42/35/22	42/35/22	43/36/23	44/37/25
	Heating		41/36/26	41/36/26	41/36/27	42/37/30
Air flow volume (Hi/Me/Lo)	Cooling	m³/h	510/420/300	510/420/300	510/420/300	540/450/300
	Heating		480/420/330	480/420/330	480/420/330	510/420/360
<b>Optional parts</b>						
Wi-Fi module			INWFIUNIO011000			
Interface for home automation connection and wired control			Not available for this product			