



Model	Indoor unit		FDE~VH / FDT~VH		
	V-Multi combinations		40+40		
	Outdoor unit		FDC 71 VNX-W		
Rated capacity (T=35°C)	Cooling	kW	7.10		
Rated power input (T=35°C)		kW	1.63		
Rated energy efficiency coefficient		EER ¹	4.36		
Rated capacity (T=7°C)	Heating	kW	8.00		
Rated power input (T=7°C)		kW	1.85		
Rated energy efficiency coefficient		COP ¹	4.32		
Installation accessories			DIS-WA1G		
Controls			RC-EX3A / RC-E5		

Model	Indoor unit		FDE~VH / FDT~VH		
	V-Multi combinations		50+50		
	Outdoor unit		FDC 100 VSX-W		
Rated capacity (T=35°C)	Cooling	kW	10.00		
Rated power input (T=35°C)		kW	2.47		
Rated energy efficiency coefficient		EER ¹	4.05		
Rated capacity (T=7°C)	Heating	kW	11.20		
Rated power input (T=7°C)		kW	2.87		
Rated energy efficiency coefficient		COP ¹	3.90		
Installation accessories			DIS-WA1G		
Controls			RC-EX3A / RC-E5		

Model	Indoor unit		FDE~VH / FDT~VH		
	V-Multi combinations		60+60	50+71	
	Outdoor unit		FDC 125 VSX-W		
Rated capacity (T=35°C)	Cooling	kW	12.50	12.50	
Rated power input (T=35°C)		kW	3.48	3.45	
Rated energy efficiency coefficient		EER ¹	3.59	3.62	
Rated capacity (T=7°C)	Heating	kW	14.00	14.00	
Rated power input (T=7°C)		kW	3.26	3.24	
Rated energy efficiency coefficient		COP ¹	4.29	4.32	
Installation accessories			DIS-WA1G		
Controls			RC-EX3A / RC-E5		

Model	Indoor unit		FDE~VH / FDT~VH		
	V-Multi combinations		71+71		
	Outdoor unit		FDC 140 VSX-W		
Rated capacity (T=35°C)	Cooling	kW	14.00		
Rated power input (T=35°C)		kW	4.16		
Rated energy efficiency coefficient		EER ¹	3.37		
Rated capacity (T=7°C)	Heating	kW	16.00		
Rated power input (T=7°C)		kW	4.12		
Rated energy efficiency coefficient		COP ¹	3.88		
Installation accessories			DIS-TA1G		
Controls			RC-EX3A / RC-E5		

1 Value measured according to harmonised standard EN14511.

BRANCH PIPE KIT

DIS-WA1G	DIS-WB1G	DIS-TA1G	DIS-TB1G
Gas side 	Gas side 	Gas side 	Gas side 
Liquid side 	Liquid side 	Liquid side 	Liquid side 
Reducer 	Reducer 	Reducer 	