

# INDOOR UNITS

## DUCTED LOW STATIC PRESSURE



SRR 25-35-50-60 ZS-W



OPTIONAL



&lt;REMOTE CONTROL INCLUDED&gt;

| Model                                                                   |              |            | SRR 25 ZS-W             | SRR 35 ZS-W             | SRR 50 ZS-W              | SRR 60 ZS-W              |
|-------------------------------------------------------------------------|--------------|------------|-------------------------|-------------------------|--------------------------|--------------------------|
| Type                                                                    |              |            | Ducted type indoor unit |                         |                          |                          |
| Control                                                                 |              |            | Remote control          |                         |                          |                          |
| Rated capacity                                                          | Cooling      | kW         | 2.50                    | 3.50                    | 5.00                     | 6.00                     |
|                                                                         | Heating      | kW         | 3.40                    | 4.50                    | 5.80                     | 6.80                     |
| <b>Electrical data</b>                                                  |              |            |                         |                         |                          |                          |
| Power supply                                                            | Outdoor unit | Ph-V-Hz    | 1-220~240V-50Hz         |                         |                          |                          |
| Wiring cables I.U./O.U.                                                 |              | nb.        | 4                       | 4                       | 4                        | 4                        |
| <b>Refrigerant circuit data</b>                                         |              |            |                         |                         |                          |                          |
| Diameter of refrigerant pipings liquid/gas                              |              | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") | 6.35(1/4") - 12.74(1/2") |
| <b>Product specifications</b>                                           |              |            |                         |                         |                          |                          |
| Dimensions                                                              | LxDxH        | mm         | 750x500x200             | 750x500x200             | 950x500x200              | 950x500x200              |
| Net weight                                                              |              | Kg         | 20.5                    | 20.5                    | 24                       | 24                       |
| Sound power level (Hi)                                                  | Cooling      | dB(A)      | 56                      | 57                      | 59                       | 60                       |
|                                                                         | Heating      |            | 59                      | 60                      | 61                       | 63                       |
| Sound pressure level (Hi/Me/Lo/ULo)                                     | Cooling      | dB(A)      | 37/33/30/24             | 38/34/31/25             | 41/37/34/29              | 44/38/35/30              |
|                                                                         | Heating      |            | 40/37/34/28             | 42/38/35/29             | 43/39/37/32              | 45/41/38/33              |
| Air flow volume (Hi/Me/Lo/ULo)                                          | Cooling      | m³/h       | 570/480/390/270         | 600/510/420/300         | 810/660/600/450          | 870/690/630/480          |
|                                                                         | Heating      |            | 600/540/480/360         | 630/570/510/390         | 840/750/660/510          | 900/780/690/540          |
| Fan static pressure                                                     | Std/Max      | Pa         | 5/35                    | 5/35                    | 5/50                     | 5/50                     |
| <b>Optional parts</b>                                                   |              |            |                         |                         |                          |                          |
| Wi-Fi module <sup>1</sup>                                               |              |            | WF-RAC                  |                         |                          |                          |
| Interface for home automation connection and wired control <sup>2</sup> |              |            | SC-BIKN2-E              |                         |                          |                          |
| Kit for recovery from bottom                                            |              |            | UT-BAT1EF               |                         | UT-BAT2EF                |                          |

1. Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.

2. Home automation protocols available: KNX, Modbus, BACnet.

## CONSOLE

SRF 25-35 ZS-W  
SRF 50 ZSX-W

OPTIONAL



&lt;REMOTE CONTROL INCLUDED&gt;

| Model                                                       |              |            | SRF 25 ZS-W             | SRF 35 ZS-W             | SRF 50 ZSX-W             |
|-------------------------------------------------------------|--------------|------------|-------------------------|-------------------------|--------------------------|
| Type                                                        |              |            | Floor type indoor unit  |                         |                          |
| Control                                                     |              |            | Remote control          |                         |                          |
| Rated capacity                                              | Cooling      | kW         | 2.50                    | 3.50                    | 5.00                     |
|                                                             | Heating      | kW         | 3.40                    | 4.50                    | 5.80                     |
| Electrical data                                             |              |            |                         |                         |                          |
| Power supply                                                | Outdoor unit | Ph-V-Hz    | 1-220~240V-50Hz         |                         |                          |
| Wiring cables I.U./O.U.                                     |              | nb.        | 4                       | 4                       | 4                        |
| Refrigerant circuit data                                    |              |            |                         |                         |                          |
| Diameter of refrigerant pipings liquid/gas                  |              | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") |
| Product specifications                                      |              |            |                         |                         |                          |
| Dimensions                                                  | LxDxH        | mm         | 860x238x600             | 860x238x600             | 860x238x600              |
| Net weight                                                  |              | Kg         | 18                      | 19                      | 19                       |
| Sound power level (Hi)                                      | Cooling      | dB(A)      | 50                      | 51                      | 58                       |
|                                                             | Heating      |            | 51                      | 52                      | 58                       |
| Sound pressure level (Hi/Me/Lo/ULo)                         | Cooling      | dB(A)      | 38/32/29/25             | 40/35/33/29             | 46/38/33/28              |
|                                                             | Heating      |            | 39/35/33/39             | 41/36/35/33             | 46/41/38/32              |
| Air flow volume (Hi/Me/Lo/ULo)                              | Cooling      | m³/h       | 540/456/402/348         | 552/468/438/384         | 690/576/444/396          |
|                                                             | Heating      |            | 630/492/462/396         | 642/498/486/444         | 720/600/564/456          |
| Optional parts                                              |              |            |                         |                         |                          |
| Wi-Fi module¹                                               |              |            | WF-RAC                  |                         |                          |
| Interface for home automation connection and wired control² |              |            | SC-BIKN2-F              |                         |                          |

1. Using the Wi-Fi module excludes the possibility of connecting any other optional accessory.

2. Home automation protocols available: KNX, Modbus, BACnet.