

INDOOR UNITS

WALL



SRK 71-80 ZR-WF



<INCLUDED>



<REMOTE CONTROL INCLUDED>

Model			SRK 71 ZR-WF	SRK 80 ZR-WF
Type			Wall type indoor unit	
Control			Remote control	
Rated capacity	Cooling	kW	7.10	8.00
	Heating	kW	8.00	9.00
Electrical data				
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz	
Wiring cables I.U./O.U.		nb.	4	4
Refrigerant circuit data				
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 15.88(5/8")	
Product specifications				
Dimensions	LxDxH	mm	1197x262x339	1197x262x339
Net weight		Kg	15.5	16.5
Sound power level (Hi)	Cooling	dB(A)	57	60
	Heating		60	62
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	44/41/37/25	47/44/39/26
	Heating		46/39/35/28	47/41/36/29
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m³/h	1230/1116/972/624	1410/1212/1050/624
	Heating		1500/1188/1038/798	1590/1278/1104/810
Optional parts				
Wi-Fi module			Included	
Interface for home automation connection and wired control¹			SC-RKN2-F	

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

WALL



SKM 15-20-25-35 ZSP-W



OPTIONAL



<REMOTE CONTROL INCLUDED>

Model			SKM 15 ZSP-W	SKM 20 ZSP-W	SKM 25 ZSP-W	SKM 35 ZSP-W
Type			Wall type indoor unit			
Control			Remote control			
Rated capacity	Cooling	kW	1.50	2.00	2.50	3.50
	Heating	kW	2.00	3.00	3.40	4.50
Electrical data						
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz			
Wiring cables I.U./O.U.		nb.	4	4	4	4
Refrigerant circuit data						
Diameter of refrigerant pipings liquid/gas		mm (inch.)	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")	6.35(1/4") - 9.52(3/8")
Product specifications						
Dimensions	LxDxH	mm	783x210x267	783x210x267	783x210x267	783x210x267
Net weight		Kg	7.5	7.5	7.5	7.5
Sound power level (Hi)	Cooling	dB(A)	57	57	57	58
	Heating		56	56	56	58
Sound pressure level (Hi/Me/Lo/ULo)	Cooling	dB(A)	42/35/22	42/35/22	43/36/23	44/37/25
	Heating		41/36/26	41/36/26	41/36/27	42/37/30
Air flow volume (Hi/Me/Lo/ULo)	Cooling	m³/h	510/420/300	510/420/300	510/420/300	540/450/300
	Heating		480/420/330	480/420/330	480/420/330	510/420/360
Optional parts						
Modulo Wi-Fi			INWFIUN0011000			
Interface for home automation connection and wired control			Not available for this product			