

# INDOOR UNITS

## KIREIA Plus WALL



SRK 20-25-35-50-60 ZSX-WF(T)



INCLUDED



Remote control included

| Model                                                       |              |            | SRK 20 ZSX-WF(T)        | SRK 25 ZSX-WF(T)        | SRK 35 ZSX-WF(T)        | SRK 50 ZSX-WF(T)         | SRK 60 ZSX-WF(T)         |
|-------------------------------------------------------------|--------------|------------|-------------------------|-------------------------|-------------------------|--------------------------|--------------------------|
| Type                                                        |              |            | Wall type indoor unit   |                         |                         |                          |                          |
| Control                                                     |              |            | Remote control          |                         |                         |                          |                          |
| Rated capacity                                              | Cooling      | kW         | 2.00                    | 2.50                    | 3.50                    | 5.00                     | 6.00                     |
|                                                             | Heating      | kW         | 3.00                    | 3.40                    | 4.50                    | 5.80                     | 6.80                     |
| Electrical data                                             |              |            |                         |                         |                         |                          |                          |
| Power supply                                                | Outdoor unit | Ph-V-Hz    | 1-220~240V-50Hz         |                         |                         |                          |                          |
| Wiring cables I.U./O.U.                                     |              | nb.        | 4                       | 4                       | 4                       | 4                        | 4                        |
| Refrigerant circuit data                                    |              |            |                         |                         |                         |                          |                          |
| Diameter of refrigerant pipings liquid/gas                  |              | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") | 6.35(1/4") - 12.74(1/2") |
| Product specifications                                      |              |            |                         |                         |                         |                          |                          |
| Dimensions                                                  | LxDxH        | mm         | 920x220x305             | 920x220x305             | 920x220x305             | 920x220x305              | 920x220x305              |
| Net weight                                                  |              | Kg         | 13                      | 13                      | 13                      | 13                       | 13                       |
| Sound power level (Hi)                                      | Cooling      | dB(A)      | 53                      | 55                      | 58                      | 59                       | 62                       |
|                                                             | Heating      |            | 55                      | 56                      | 58                      | 62                       | 63                       |
| Sound pressure level (Hi/Me/Lo/U/Lo)                        | Cooling      | dB(A)      | 38/31/24/19             | 39/33/25/19             | 43/35/26/19             | 44/39/31/22              | 48/41/33/22              |
|                                                             | Heating      |            | 38/33/25/19             | 40/34/27/19             | 42/35/28/19             | 47/41/33/23              | 47/42/34/23              |
| Air flow volume (Hi/Me/Lo/U/Lo)                             | Cooling      | m³/h       | 678/546/360/300         | 732/600/402/300         | 786/648/438/300         | 858/744/468/324          | 978/804/534/324          |
|                                                             | Heating      |            | 732/618/432/324         | 768/660/468/324         | 834/708/516/324         | 1038/858/588/372         | 1068/822/654/372         |
| Optional parts                                              |              |            |                         |                         |                         |                          |                          |
| Wi-Fi module                                                |              |            | Included                |                         |                         |                          |                          |
| Interface for home automation connection and wired control¹ |              |            | SC-BIKN2-E              |                         |                         |                          |                          |

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.

## KIREIA WALL



SRK 15-20-25-35-50 ZS-WF(T)



INCLUDED



Remote control included

| Model                                                                   |              |            | SRK 15 ZS-WF(T)         | SRK 20 ZS-WF(T)         | SRK 25 ZS-WF(T)         | SRK 35 ZS-WF(T)         | SRK 50 ZS-WF(T)          |
|-------------------------------------------------------------------------|--------------|------------|-------------------------|-------------------------|-------------------------|-------------------------|--------------------------|
| Type                                                                    |              |            | Wall type indoor unit   |                         |                         |                         |                          |
| Control                                                                 |              |            | Remote control          |                         |                         |                         |                          |
| Rated capacity                                                          | Cooling      | kW         | 1.50                    | 2.00                    | 2.50                    | 3.50                    | 5.00                     |
|                                                                         | Heating      | kW         | 2.00                    | 3.00                    | 3.40                    | 4.50                    | 5.80                     |
| Electrical data                                                         |              |            |                         |                         |                         |                         |                          |
| Power supply                                                            | Outdoor unit | Ph-V-Hz    | 1-220~240V-50Hz         |                         |                         |                         |                          |
| Wiring cables I.U./O.U.                                                 |              | nb.        | 4                       | 4                       | 4                       | 4                       | 4                        |
| Refrigerant circuit data                                                |              |            |                         |                         |                         |                         |                          |
| Diameter of refrigerant pipings liquid/gas                              |              | mm (inch.) | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 9.52(3/8") | 6.35(1/4") - 12.74(1/2") |
| Product specifications                                                  |              |            |                         |                         |                         |                         |                          |
| Dimensions                                                              | LxDxH        | mm         | 870x230x290             | 870x230x290             | 870x230x290             | 870x230x290             | 870x230x290              |
| Net weight                                                              |              | Kg         | 9.5                     | 9.5                     | 9.5                     | 9.5                     | 10                       |
| Sound power level (Hi)                                                  | Cooling      | dB(A)      | 48                      | 48                      | 50                      | 54                      | 59                       |
|                                                                         | Heating      |            | 50                      | 50                      | 53                      | 56                      | 60                       |
| Sound pressure level (Hi/Me/Lo/U/Lo)                                    | Cooling      | dB(A)      | 34/25/22/19             | 34/25/22/19             | 36/28/23/19             | 40/30/26/19             | 46/36/29/22              |
|                                                                         | Heating      |            | 36/29/23/19             | 36/29/23/19             | 39/30/24/19             | 41/36/25/19             | 46/37/31/24              |
| Air flow volume (Hi/Me/Lo/U/Lo)                                         | Cooling      | m³/h       | 558/420/354/300         | 558/420/354/300         | 594/480/354/300         | 678/522/420/300         | 726/594/444/354          |
|                                                                         | Heating      |            | 600/510/390/354         | 600/510/390/354         | 678/522/402/354         | 738/660/420/336         | 834/672/546/444          |
| Optional parts                                                          |              |            |                         |                         |                         |                         |                          |
| Wi-Fi module                                                            |              |            | Included                |                         |                         |                         |                          |
| Interface for home automation connection and wired control <sup>1</sup> |              |            | SC-BIKN2-F              |                         |                         |                         |                          |

1. Available home automation protocols: KNX, Modbus, BACnet. The use of the interface card SC-BIKN2-E forbids some indoor unit functions. Keep in touch with your contact person for further information.